

HEADQUARTERS

FAAC spa
Via Calari 10 40069 Zola Predosa (BO)
Tel. +39 051 61724 - Fax +39 051 758518
info@faac.it - www.faacgroup.com

FAAC SUBSIDIARIES

FAAC AG
Tel. +41 52 3461721
Fax +41 52 3461723
Illnau, Switzerland
www.faac.ch

FAAC FRANCE
Tel. +33 472218700
Fax +33 472218701
Corbas, France
www.faac.fr

FAAC GMBH
Tel. +49 8654 49810
Fax +49 8654 498125
Freilassing, Germany
www.faac.de

FAAC MIDDLE EAST
Dubai, Emirati Arabi
www.faac.ae
info@faac.ae

FA.A.C. SA
Tel. +34 91 6613112
Fax +34 91 6610050
Madrid, España
www.faac.es

FAAC UK LTD.
Tel. +44 1256 318100
Fax +44 1256 318101
Basingstoke Hampshire, UK
www.faac.co.uk

FAAC AUSTRALIA PTY LTD
Tel. +61 2 7565644
Fax +61 2 87565677
Homebush – Sydney, Australia
www.faac.com.au

FAAC NORD
Tel. +33 1 69191620
Fax +33 1 69536069
Massy, France
www.faac.fr

FAAC INDIA PVT. LTD
Tel. +91 120 3934100/4199
Fax +91 120 4212132
Noida – Delhi, India
www.faacindia.com

FAAC POLSKA SP.ZO.O.
Tel. +48 22 8141125
Fax +48 22 8142024
Warszawa, Polska
www.faac.pl

FA.A.C. SA Delegación Cataluña
Tel. +34 93 4362000
Fax +34 93 5727994/4368225
Barcelona, España
www.faac.es

FAAC BENELUX
Tel. +32 50 320202
Fax +32 50 32024215
Brugge, Belgium
www.faac.be

FAAC G.E.S. M.B.H.
Tel. +43 662 8533950
Fax +43 662 85339520
Wals – Siezenheim, Austria
www.faac.at

FAAC INTERNATIONAL INC.
Tel. +1 307 6351991
Fax +1 307 6328148
Cheyenne, USA
www.faacusa.com

FAAC SCANDINAVIA AB
Tel. +46 36 376860
Fax +46 36 370780
Bankeryd, Sweden
www.faac.se

FAAC SHANGHAI
Tel. +86 21 68182970
Fax +86 21 68182968
Shanghai, China
www.faac.com.cn

908475004 - Rev. 10 - 3.000 - Zucchini - 01/2009 The descriptions and illustrations contained in the present brochure are not binding. FAAC reserve the right to undertake product technical modifications without prior notice.



615

Hydraulic barrier system for beams up to 5m

FAAC



THE 615 AUTOMATIC BARRIER SUITABLE FOR BEAMS UP TO 5M

- Neat slimline appearance
- Specifically deisgned for medium transit frequency
- Anti-crushing hydraulic safety device
- Highly reliable due to a combination of testing and quality assurance at ISO9001 registered standard.



Fork support



Adjustable fork support with mag lock



Adjustable pogo stick



Dimensions of the unit.





Diagram of beam mounting



TECHNICAL SPECIFICATIONS 615

	615 Standard	615 Rapid
Motor supply	230 Vac	
Absorbed Power	220 W	
Absorbed Current	1A	
Motor rotation speed	1,400 rpm	2,800 rpm
Pump flow rate	1.5 l/min	3l/min
Thermal protection on motor winding	120°C	
Dimensions (LxDxH)	270 x 140 x 1015	
Thrust capacitor	8uF 400V	16uF 400V
max beam length	5m	2.5m

	615 standard	615 Rapid
Operating ambient temperature	-20°C ÷ +55°C	
Weight	34 Kg	
Type of oil	FAAC HP Oil	
Barrier body treatment	Cataphoresis	
Paint	Polyester RAL 2004	
protection class	IP44	
Max consec. cycles	220	340
Use frequency	50%	40%
Type of rectangular beam	standard- standard with skirt (4m) - articulated standard	standard